

# Orford EB36R-C Flower Fridge



Proudly Australian Designed by

**Orford Refrigeration** 

IP protected by AUS DSN no 345317



Orford Refrigeration continues to develop World Class Energy reduction systems to improve the lives of our customers and future generations.



**1300 ORFORD (1300 673 673)** 

+617 4641 7372

sales@orford.com.au
www.orford.com.au







## Orford EB36R-C Flower Fridge

## **Features**


- World Class Design
- World Class Energy Efficiency
- World Class Performance, Quality &
  - Reliability
- Universal Refrigeration Package
- One package fits the entire EB Range
- Cassette Style : Removable without tools
- Minimal training required for nonqualified personal to replace the package

## **Features**


- Independent light switch via switch or via controller
- Condenser Filter—Easy access to filter with NO tools or covers to remove
- Carel Ezy Controller








With Evolution comes much responsibility. Orford continues to develop World Class Energy reduction systems to improve the lives of our customers and future generations.





\* Energy Consumption measured at 25°C. Cabinet Class 3M1 as per Australian Standard AS1731

### EB36R-Sn Flower FlowerDisplay Refrigerator **Specifications** with Illuminated Advertising Sign Powder Coated galvanized steel Construction Interior /Exterior White 1071 Litres (Gross) Capacity **Dimensions** 1286W x 762D x 2220H Weight 221Kg 4° - 8° C. **Operating Temp** Ambient Temp Range 0° - 40° C. **Power Point** 220 - 240v 50Hz. (Standard GPO) Input Current 2.9 Amps Thermometer Digital—Carel Ezy 8 Height Adjustable Heavy Duty PVC Coated Shelves 2 Fixed Stainless Steel Base Shelves Shelves Shelf Adjustment 12mm Increments Refrigerated Shelf Area 2.62 m<sup>2</sup> Condensate Disposal Automatic by energy efficient, No Cost, Hot Gas 2 x Self Closing, Double Glazed Safety Glass, Door Double Heat reflective Low E, Warm edge **Footings** Heavy Duty Castors, Lockable Front Interior Light LED, with independent light switches R134a Refrigerant Drier Solid Core Insulation 50mm Polyurethane, CFC, HCFC, HFC Free Cabinet Classes 3M1, 4M1, 5M1 MFPS Compliant (High Efficiency) \* Energy Consumption 4.74 kWh/24h Condenser Filter Easy front access Illuminated Advertising Sign 200mm High, Top Mounted Sign Illumination LED, Automatic and manual control

1300 ORFORD (1300 673 673) +617 4641 7372

sales@orford.com.au

