

Proudly Australian Designed

by The Orford Group



With Evolution comes much responsibility. The Orford Group continues to develop World Class Energy reduction systems to improve the lives of our customers and future generations.







+617 4641 7372



Features

World class,

- > Design
- > Energy Efficiency
- > Performance
- Quality
- Reliability

Universal Refrigeration Package

- ➤ One package fits the entire **FB** Range
- > Cassette Style: Removable without tools
- Minimal training required for non-qualified personal to replace the package

Energy Management System (EMS)

- Automatically learns you trading times
- Automates your energy savings
- > Perishable and non-perishable mode

Lighting Control

- > Automated or manual control, you choose
- > Independent switching of interior lighting

Condenser Fan Function


Your choice of reversing or non-reversing function


Condenser Filter


Easy Access filter: No tools, no covers to remove

High Energy Efficiency

	<u> </u>
EB30R Flower Specifications	Vertical Display Refrigerator
Construction	Powder Coated galvanized steel
	Interior / Exterior White
Capacity	895 Litres (Gross)
Dimensions	1094W x 762D x 2020H
Weight	210Kg
Operating Temp	4° - 8° C.
Ambient Temp Range	0° - 40° C.
Power Point	220 - 240v 50Hz. (Standard GPO)
Input Current	2.8 Amps
Thermometer	Digital
Shelves	8 Height Adjustable Heavy Duty PVC Coated
Shelves	2 Fixed Stainless Steel Base Shelves
Shelf Adjustment	12mm Increments
Refrigerated Shelf Area	2.17 m ²
Condensate Disposal	Automatic by energy efficient, No Cost, Hot Gas
Door	2 x Self Closing, Double Glazed Safety Glass,
	Double Heat reflective Low E, Warm edge
Footings	Heavy Duty Castors, Lockable Front
Interior Light	LED Automatic and manual control
Refrigerant	R134a
Drier	Solid Core
Insulation	50mm Polyurethane, CFC, HCFC, HFC Free
Cabinet Classes	3M1, 4M1, 5M1
MEPS	Compliant (High Efficiency)
* Energy Consumption	3.79 kWh/24h
Condenser Filter	Easy front access







* Energy Consumption measured at 25°C. Cabinet Class 3M1 as per Australian Standard AS1731

IP protected by AUS DSN no 345317

1300 ORFORD (1300 673 673) +617 4641 7372

sales@orford.com.au www.orford.com.au





Queensland 4350 Australia